



VIEW

**SAGEX (033) DS 150**  
**SAGEX Druckfeste Dämmplatten**  
**Sager AG**

<http://www.sager.ch/> | [info@sager.ch](mailto:info@sager.ch)

**Type:    Insulation | Polystyrol**

hochentwickelte Dämmplatte aus EPS mit sehr hoher Druckspannung.

Expandierte Polystyrolplatten für Unterlagsböden mit sehr hoher Druckspannung.

mtextur ID	20453
Manufacturer	Sager AG
Manufacturer-Email	<a href="mailto:info@sager.ch">info@sager.ch</a>
Product Line	SAGEX Druckfeste Dämmplatten
Product Line Info	Expandierte Polystyrolplatten für Unterlagsböden mit sehr hoher Druckspannung.
Material Name	SAGEX (033) DS 150
Type	Insulation / Polystyrol
Material Info	hochentwickelte Dämmplatte aus EPS mit sehr hoher Druckspannung.
eBKP	C 1.2 Waterproofing/insulation below ground slab
IFC	lfcCovering / lfcSlab.Floor
Area of application (mtextur Classic)	Inside / Ceiling / Floor
Delivery zones	LI / CH
Size of the CAD & BIM texture	Height: 500.0 mm / Width: 500.0 mm

## IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.

max. Length / Format	Length = 1000 mm / Width = 500 mm / Thickness = 40 mm
min. Format	Length = 700 mm / Width = 500 mm / Thickness = 20 mm
Weight	25.0 kg/m <sup>3</sup>
Thermal Conductivity	0.033 W/mK
Fire protection class	5.1,RF2 (cr) E
Characteristics Info	Anwendungsgebiet: Innendämmung der Decke oder Bodenplatte (oberseitig) unter Estrich ohne Schallschutzanforderungen

**IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:**

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.