



CUT LENGTHWISE



CUT CROSSWISE

VIEW

SAGLAN (031) SB 55

SAGLAN Dämmplatten

Sager AG

<http://www.sager.ch/> | info@sager.ch

Type: **Insulation | Cemented**

Mit Strichmarkierung

Für SAGLAN Glaswolle wird natürlicher Quarzsand geschmolzen, zu feinen Glasfasern versponnen und zu unbrennbaren Glaswolleplatten oder Rollfilzen weiterverarbeitet. Diverse Beschichtungen, wie z.B. Glasvlies oder Aluminium erweitern den Einsatzbereich unsere Glaswolle Produkte. Mit SAGLAN Glaswolle erreicht man einen ausgezeichneten Schallschutz und Wärmedämmwert.

mtextur ID	20980
Manufacturer	Sager AG
Manufacturer-Email	info@sager.ch
Product Line	SAGLAN Dämmplatten
Product Line Info	Für SAGLAN Glaswolle wird natürlicher Quarzsand geschmolzen, zu feinen Glasfasern versponnen und zu unbrennbaren Glaswolleplatten oder Rollfilzen weiterverarbeitet. Diverse Beschichtungen, wie z.B. Glasvlies oder Aluminium erweitern den Einsatzbereich unsere Glaswolle Produkte. Mit SAGLAN Glaswolle erreicht man einen ausgezeichneten Schallschutz und Wärmedämmwert.
Material Name	SAGLAN (031) SB 55
Type	Insulation / Cemented
Material Info	Mit Strichmarkierung
eBKP	C 1.2 Waterproofing/insulation below ground slab / C 2.1 External walls / C 4.4 Roof structure, roof slabs
IFC	IfcCovering / IfcSlab / IfcWall / IfcSlab.Floor
Area of application (mtextur Classic)	Inside / Wall / Ceiling / Roof / Facade / Floor Outside / Wall / Ceiling / Roof / Facade / Floor
Delivery zones	LI / CH
Size of the CAD & BIM texture	Height: 400.0 mm / Width: 400.0 mm

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.

max. Length / Format	Length = 1250 mm / Width = 600 mm / Thickness = 160 mm
min. Format	Length = 1250 mm / Width = 600 mm / Thickness = 30 mm
Weight	52.0 kg/m ³
Thermal Conductivity	0.031 W/mK
Fire protection class	6q.3 A1
Characteristics Info	Steife Dämmplatten, durchgehend imprägniert. Wärme- und Schalldämmung für hinterlüftete Fassaden oder Rauntrennwände. Beim Dach für Sparrendach auf der Schalung, Beton- oder Hallensteildach auf Profilblech.

IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.